



Product Service

CERTIFICATE

No. U8V 06 10 21477 011

Holder of Certificate: Westcor Corporation

560 Oakmead Parkway
Sunnyvale CA 94085-4022
USA

Production Facility(ies): 21477, 21433

Certification Mark:



Product: Power supplies
Switching Power Supply

Model(s): PC2-02-3468-G (PFC Micro and Micro S Series)
See attachment for model differences
and license conditions.

Parameters:

Rated Input Voltage:	115-230 V AC/300 V DC
Rated Frequency:	47-500 Hz
Rated Input Current:	7.5 A/7.5 A
Rated Output Voltage:	0-95 V DC
Rated Output Power:	800 W Max.

Tested according to: CSA-C 22.2 No. 60950-1-03
UL 60950-1:2003
EN 60950-1:2001

The product was voluntarily tested according to the relevant safety requirements and mentioned properties. It can be marked with the certification mark shown above. The certification mark must not be altered in any way. See also notes overleaf.

Test report no.: DI605769-101

Date, 2006-10-31

Page 1 of 2





Product Service

Attachment 1 to U8V 06 10 21433 011

Company: Westcor Corporation
 560 Oakmead Parkway
 Sunnyvale CA 94085

PFC Micro and Micro S Series Model Pxa-bc-dddd-e-f

Item 0. Series Type	Input Voltage	Max Output Power
x = S for Micro S	115 Vac	500 W
	230 Vac or 300 Vdc	600 W
x = C for Micro	115 Vac	500 W
	230 Vac or 300 Vdc	800 W

Item 1. Number of Outputs

a = Total number of outputs (note: 3 for PC or 6 for PS), rated 0-95 Vdc each

Item 2. Module Configuration

b = Total number of VI-200 and/or VI-J00 Series DC/DC Converters

c = Total number of 2nd Gen FasTrack Series DC/DC Converters

Item 3. Factory assigned Code (Non-safety related)

dddd = can be any alphanumeric combination or blanks

Item 4. Configuration Revision (Optional)

e = can be any alphanumeric combination or blank (note: e = G for RoHs compliant)

Item 5. Micro description (Optional)

f = can be any alphanumeric combination or blank

License Conditions:

1. The PFC Micro and Micro S are designed for building-in and must be installed in accordance with the manufacturer's instructions
2. The maximum baseplate temperature of the VI-200 Modules is 85 °C
3. The maximum baseplate temperature of the VI-J and 2nd Gen FasTrack Modules is 100 °C
4. Output voltages ≤ 60 Vdc meet the requirements of SELV
5. Output voltages > 60 Vdc are non-SELV and should be considered hazardous secondary
6. Exception to conditions 4 & 5, VI-J outputs are limited to ≤ 40 Vdc to be considered SELV

11/02/06

